

TITLE OF THE INVENTION

IMAGE DISPLAY APPARATUS AND METHOD, INFORMATION
PROCESSING APPARATUS USING THE IMAGE DISPLAY APPARATUS,
5 AND STORAGE MEDIUM

BACKGROUND OF THE INVENTION

Field of the Invention

10 This invention relates to an image display
apparatus and method, an information processing
apparatus using the image display apparatus, and a
storage medium storing a program for implementing the
method.

15

Description of the Related Art

With development of multimedia in recent years,
displays have come to be widely used in various scenes.
Widespread use of devices using image sources in new
20 digital formats, such as HDTV (High-Definition TV),
MPEG, or JPEG, and sophistication of three-dimensional
graphics not only increase the variety of processable
images, but also make it possible to use displays in
fields where no displays were conventionally used,
25 thereby increasing the range of uses of displays.

For instance, projectors have come to be widely
used at meetings or conferences and presentations. The

projectors have been rapidly taking the place of conventional OHP's and prevailing with development of notebook personal computers (personal computer(s) will be hereinafter simply referred to as "PC" or "PC's") and software for use in presentation. Further, the projectors have been changing in manners of connection with presentation tools, such as digital cameras, and other digital devices, as well as in functions thereof.

Another example is the improvement of display sections of portable information terminals. With increase in the number of pixels and the size of a screen, proliferation of color displays, and enhancement in gradation, the functions of such terminals have become more sophisticated and becoming closer to those of PC's.

In this situation, there are an increasing number of occasions when large-screen displays are used in classrooms, offices, homes and other places to provide various image sources e.g. of presentations, various data, video conferences, videos, and movies.

Particularly at school and at office meetings, a display apparatus is conveniently used which is not only capable of displaying image information but also functioning as a whiteboard for displaying on a screen information plotted by a teacher or a person presiding a meeting by using an input device such as a digitizer pen.

FIG. 1 is a conceptual representation of a large-screen rear projection display used in a classroom or an office in place of a blackboard or a whiteboard, as an example of displays conventionally used on the
5 above-mentioned occasions, while FIG. 2 shows the construction of the display.

In FIG. 1, reference numeral 601 designates an expositor, and reference numeral 602 a digitizer pen. Reference numeral 603 designates a line plotted on a
10 screen in response to an image-plotting operation by the digitizer. Reference numeral 604 designates a screen of the large-screen display, which will be described in detail with reference to FIG. 2. Further, reference numerals 605 to 607 designate a plurality of
15 windows (virtual child screens) on the PC display screen. In the illustrated example, a single PC is operated, and screens are displayed on the screen 604 according to respective application programs executed by the single PC.

20 In FIG. 2, reference numeral 701 designates the PC, and reference numeral 702 the large-screen rear projection display with the screen 604 appearing in FIG. 1. Reference numeral 704 designates digitizer detection means for detecting an image-plotting signal
25 from the digitizer pen 602. Reference numeral 705 designates an output terminal via which an image signal is outputted from the PC, and reference numeral 706 a

mouse input terminal functioning as a control signal input terminal via which the signal from the digitizer detection means 704 is inputted as a control signal for controlling the PC. Further, reference numeral 707
5 designates an operating system (OS) (1) of the PC 701, and reference numeral 708 an application program (1) which is one of application software programs operated on the PC 701. Reference numeral 709 designates a whiteboard software program (1) which is also one of
10 the application software programs operated on the PC 701, particularly for realizing a whiteboard function on the PC 701. Actually, the OS (1) 707, the application program (1) 708 and the whiteboard software program (1) 709 are stored and exist as software
15 programs in a storage medium for the PC 701. However, they are shown as false images in FIG. 2 to represent their operations on the PC 701.

Reference numeral 710 designates an image input terminal of the display 702, and reference numeral 711
20 an input image signal processing section. When an input signal is an analog signal, the input image signal processing section 711 performs adjustment of the input image signal to a predetermined amplitude and a predetermined DC level and converts the analog signal
25 to a digital signal, while when an input signal is a digital signal, the section 711 performs conversion of the signal to a predetermined signal level and to a

predetermined color format, and other processing.

Reference numeral 712 designates a resolution conversion section that performs conversion of the resolution and frame rate of the image signal,

5 reference numeral 713 an output image processing section that performs signal processing, such as gamma correction and division driving suitable for a device forming an image display section, and reference numeral 714 the image display section comprised of a device,
10 such as a liquid crystal display, a cathode ray tube (CRT), or a plasma display panel (PDP), a drive circuit therefor, a light source and a projecting optical system. The section 714 corresponds to the screen 604 in FIG. 1.

15 Image-plotting operation is performed by the digitizer pen 602 on an image display surface of the image display section 714 (the screen 604), on which an image is displayed by starting and activating the whiteboard software program (1) 709 together with the
20 application (1) 708 on the OS (1) 707 of the PC 701. The image-plotting signal generated by the digitizer pen 602 is detected by the digitizer detection means 704, and a coordinate signal obtained by converting the image-plotting signal is delivered to the mouse input
25 terminal 706 to operate the whiteboard software program by mouse operation. According to the whiteboard software program, by selectively using one of tools

available on the software including a pen and an eraser, the locus of the digitizer pen 602 is plotted on the display screen of the PC 701. This causes the motion of the pen on the screen 604 of the display 702 to agree with the locus of the pen on the display screen of the PC 701. Thus, it is possible to handle files on the display 702 and input characters according to character recognition software by using the digitizer pen 602, whereby the whiteboard function is realized.

10 In the conventional large-screen display 702, however, the display having the whiteboard function realizes the whiteboard function by the application software program on the PC 701. Therefore, after the power of the display 702 is turned on, it takes time from the start of the PC 701 to authentication of a network to which the PC 701 belongs and a user, and hence the user has to wait to use the display 702 for a considerable time. Further, the PC 701 connected to the display 702 is shared by a number of users, so that the use of the PC 701 is required to be permitted by taking adequate security into consideration, which complicates the process of authentication of the network to which the PC 701 belongs and a user. For instance, even if children happen to want to use the whiteboard function at school for trifles, or if office workers want to use the display 702 for memo paper while talking about a simple arrangement in a casual

atmosphere, the above inconvenience at the start of the PC 701 hinders them from using the display 702.

SUMMARY OF THE INVENTION

5

It is an object of the present invention to provide an image display apparatus and method, which are capable of improving the operability of a white board function thereof, and allowing different devices
10 to be operated on the same screen in a unified manner, and an information processing apparatus having the image display apparatus, and a storage medium storing a program for implementing the method.

To attain the above object, according to a first
15 aspect of the present invention, there is provided an image display apparatus comprising a control signal input device that inputs a control signal, an operation signal output device that outputs an operation signal to an external signal source, a memory device that
20 stores display screen information, and a control signal switching device that selectively switches use of the control signal from the control signal input device between a control signal for the display screen information stored in the memory device and the
25 operation signal to be outputted from the operation signal output device.

Preferably, the control signal switching device

selectively switches the use of the control signal in a manner responsive to coordinates of a position in a display area in which the display screen information stored in the memory device is displayed, the position
5 being indicated by the control signal.

Preferably, the image display apparatus further comprises an image signal input device that inputs an image signal from the external signal source, and an image synthesis device that synthesizes the display
10 screen information stored in the memory device and a signal based on the image signal inputted by the image signal input device.

More preferably, the memory device has a plurality of areas which comprise at least an area storing
15 information based on the control signal inputted by the control signal input device, an area storing information based on the image signal inputted by the image signal input device, and information based on a signal obtained by synthesis by the image synthesis
20 device.

To attain the above object, according to a second aspect of the present invention, there is provided an image display apparatus comprising a control signal input device that inputs a control signal, an image
25 signal input device that inputs an image signal from an external signal source, an image signal processing device that processes the inputted image signal, an

image display device that displays an image based on the image signal processed by the image signal processing device, on a display screen, an operation signal output device that outputs an operation signal to the external signal source, a memory device that stores display screen information which can be rewritten by the control signal from the control signal input device, an image synthesis device that synthesizes the display screen information stored in the memory device and the image signal processed by the image signal processing device, and a control signal switching device that selectively switches use of the control signal from the control signal input device between a signal for rewriting the display screen information stored in the memory device and the operation signal to be outputted from the operation signal output device, according to an instruction from the control signal input device concerning a display area in which the display screen information stored in the memory device is displayed and a display area in which the image signal processed by the image signal processing device is displayed, the display areas being obtained by synthesis by the image synthesis device.

To attain the above object, according to a third aspect of the present invention, there is provided an information processing apparatus using the image display device according to the first aspect of the

present invention.

To attain the above object, according to a fourth aspect of the present invention, there is provided an information processing apparatus using the image
5 display apparatus according to the second aspect of the present invention.

To attain the above object, according to a fifth aspect of the present invention, there is provided an image display method comprising a control signal-
10 inputting step of inputting a control signal, an operation signal-outputting step of outputting an operation signal to an external signal source, a memory step for storing display screen information, and a control signal-switching step of selectively switching
15 use of the control signal inputted at the control signal-inputting step between a control signal for the display screen information stored at the memory step and the operation signal to be outputted at the operation signal-outputting step.

20 To attain the above object, according to a sixth aspect of the present invention, there is provided an image display method comprising a control signal-inputting step of inputting a control signal, an image signal-inputting step of inputting an image signal from
25 an external signal source, an image signal-processing step of processing the inputted image signal, an image display step of displaying an image based on the image

signal processed at the image signal-processing step,
on a display screen, an operation signal-outputting
step of outputting an operation signal to the external
signal source, a memory step of storing display screen
5 information which can be rewritten by the control
signal inputted at the control signal-inputting step,
an image-synthesizing step of synthesizing the display
screen information stored at the memory step and the
image signal processed at the image signal-processing
10 step, and a control signal-switching step of
selectively switching use of the control signal
inputted at the control signal-inputting step between a
signal for rewriting the display screen information
stored at the memory step and the operation signal to
15 be outputted at the operation signal-outputting step,
according to an instruction at the control signal-
inputting step concerning a display area in which the
display screen information stored at the memory step is
displayed and a display area in which the image signal
20 processed at the image signal-processing step, the
display areas being obtained by synthesis by the image
synthesis step.

To attain the above object, according to a seventh
aspect of the present invention, there is provided a
25 computer-readable storage medium storing a program for
executing an image display method, the program
comprising a control signal input module for inputting

a control signal from a control signal input device, an operation signal output module for outputting an operation signal to an external signal source, a memory module for storing display screen information, and a control signal switching module for selectively switching use of the control signal inputted by the control signal input module between a control signal for the display screen information stored by the memory module and the operation signal to be outputted by the operation signal output module.

To attain the above object, according to an eighth aspect of the present invention, there is provided a computer-readable storage medium storing a program for executing an image display method, the program comprising a control signal input module for inputting a control signal from a control signal input device, an image signal input module for inputting an image signal from an external signal source, an image signal processing module for processing the inputted image signal, an image display module for displaying an image based on the image signal processed by the image signal processing module, on a display screen, an operation signal output module for outputting an operation signal to the external signal source, a memory module for storing display screen information which can be rewritten by the control signal inputted by the control signal input module, an image synthesis module for

synthesizing the display screen information stored by the memory module and the image signal processed by the image signal processing module, and a control signal switching module for selectively switching use of the control signal inputted by the control signal input module between a signal for rewriting the display screen information stored by the memory module and the operation signal to be outputted by the operation signal output module, according to an instruction by the control signal input module concerning a display area in which the display screen information stored by the memory module is displayed and a display area in which the image signal processed by the image signal processing module is displayed, the display areas being obtained by synthesis by the image synthesis module.

According to the first to eight aspects of the invention, and the preferred embodiments of the first aspect of the present invention, a whiteboard function of the image display apparatus can be realized independently of the external signal source, and therefore it is possible to realize an image display apparatus which when only the whiteboard function is required, a user can readily use simply by starting the apparatus, without being troubled by complicated operation e.g. for authentication of the user at the start of a personal computer.

Preferably, the image signal processing device

includes a resolution conversion device that converts resolution of the inputted image signal.

More preferably, the image display apparatus further comprises a second memory device that stores
5 the image signal of which resolution has been converted by the resolution conversion device, and the image synthesis device synthesizes the display screen information stored in the memory device and the image signal stored in the second memory device.

10 More preferably, the control signal switching device converts display coordinates of a display area after resolution conversion on the display screen to coordinates corresponding to an image before resolution conversion, before sending the operation signal to the
15 operation signal output device.

Preferably, the image display further comprises a third memory device that stores image information obtained by synthesis by the image synthesis device.

According to the above preferred embodiments of
20 the image display apparatus, since the resolution conversion of the inputted image signal is effected, it is possible to enhance operability of the external signal source.

Preferably, the image signal-processing step
25 includes a resolution-converting step of converting resolution of the inputted image signal.

More preferably, the image display method further

comprises a second memory step of storing the image
signal of which the resolution has been converted at
the resolution-converting step, and the display screen
information stored at the memory step and the image
5 signal stored at the second memory step are synthesized
at the image-synthesizing step.

More preferably, the control signal-switching step
includes converting display coordinates of a display
area after resolution conversion on the display screen
10 to coordinates corresponding to an image before
resolution conversion, before outputting the operation
signal at the operation signal-outputting step.

Preferably, the image display method further
comprises a third memory step of storing image
15 information obtained by synthesis at the image-
synthesizing step.

The above preferred embodiments of the image
display method provide the same advantageous effects as
provided by the above preferred embodiments of the
20 image display apparatus according to the first aspect
of the present invention.

Preferably, the image signal processing module
includes a resolution conversion module for converting
resolution of the inputted image signal.

25 More preferably, the program further comprises a
second memory module for storing the image signal of
which the resolution has been converted by the

resolution conversion module, and the image synthesis module synthesizes the display screen information stored by the memory module and the image signal stored by the second memory module.

5 More preferably, the control signal switching module converts display coordinates of a display area after resolution conversion on the display screen to coordinates corresponding to an image before resolution conversion, before sending the operation signal to the
10 operation signal output module.

Preferably, the program further comprises a third memory module for storing image information obtained by synthesis by the image synthesis module.

The above preferred embodiments of the storage
15 medium provide the same advantageous effect as provided by the above preferred embodiments of the image display apparatus according to the first aspect of the present invention.

Preferably, the image display apparatus further
20 comprises a transfer device that transfers image information obtained by synthesis by the image synthesis device to an external device.

Similarly, the image display method further comprises a transfer step of transferring image
25 information obtained by synthesis at the image-synthesizing step to an external device.

Similarly, the program further comprises a

transfer module for transferring image information obtained by synthesis by the image synthesis module to an external device.

According to these preferred embodiment, the user
5 is allowed to use the same screen and the same control means to operate different apparatuses, setting of display areas, exchange of image information, and so forth, which makes it possible to realize a user-friendly and high-performance image display apparatus.

10 Preferably, the control signal switching device changes a boundary between the display area in which the display screen information stored in the memory device is displayed and the display area in which the image signal processed by the image signal processing
15 device is displayed on an image synthesized by the image synthesis device, based on the control signal from the control signal input device.

Similarly, the control signal-switching step includes changing a boundary between the display area
20 in which the display screen information stored at the memory step is displayed and the display area in which the image signal processed at the image-processing step is displayed, on an image synthesized at the image-synthesizing step, based on the control signal inputted
25 at the control signal-inputting step.

Similarly, the control signal switching module changes a boundary between the display area in which

the display screen information stored by the memory module is displayed and the display area in which the image signal processed by the image processing module is displayed on an image synthesized by the image synthesis module based on the control signal inputted by the control signal input module.

According to these preferred embodiments, it is possible to use the control signal from the same control signal input means, such as a digitizer pen, to change a boundary of each of the display area for an image plotted by the internal whiteboard function and the display area of the image signal from an external apparatus, which are displayed separately. This makes it possible to operate two apparatuses on different platforms in a unified manner by using the same display section and the same control signal input means, thereby realizing a seamless environment.

The above and other objects, features, and advantages of the present invention will become more apparent from the following detailed description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view useful in explaining a whiteboard function of a conventional image display apparatus;

FIG. 2 is a block diagram showing the construction

of a control section of the FIG. 1 image display apparatus;

FIG. 3 is a view useful in explaining the whiteboard function of an image display apparatus
5 according to a first embodiment of the present invention;

FIG. 4 is a block diagram showing the construction of a control section of the FIG. 3 image display apparatus;

10 FIG. 5 is a view useful in explaining the whiteboard function of a portable information terminal using an image display apparatus according to a second embodiment of the present invention;

FIG. 6 is a block diagram showing the construction
15 of a control section of the FIG. 5 portable information terminal;

FIG. 7 is a flowchart of an image display process which is executed by the FIG. 5 portable information terminal;

20 FIG. 8 is a continued part of the FIG. 7 flowchart; and

FIG. 9 is a continued part of the FIG. 7 and FIG. 8 flowchart.

25 DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The present invention will now be described in

detail with reference to the drawings showing embodiments thereof.

FIG. 3 is a view which is useful in explaining the whiteboard function of an image display apparatus according to a first embodiment of the present invention.

The image display apparatus according to the first embodiment is comprised of a large-screen rear projection display having a screen 101 shown in FIG. 3. This kind of display is used in place of a blackboard or a whiteboard in classrooms or in offices.

In FIG. 3, reference numeral 101 designates a screen of the large-screen rear projection display, reference numeral 102 a whiteboard screen on which an image is plotted by using the whiteboard function of the present image display apparatus, reference numeral 103 a display screen of a PC, described in detail hereinafter, connected to the display, and reference numeral 104 an expositor. Reference numeral 105 designates a digitizer pen (input device) for use in giving an explanation. Further, reference numeral 106 designates a line plotted on the screen in response to user's image-plotting operation by using the digitizer pen 105. This figure shows a scene in which the expositor 104 is giving an explanation while viewing the display screen 103 and plotting characters and a figure with the digitizer pen 105 by making use of the

whiteboard function of the present image display apparatus.

FIG. 4 shows the construction of a control section of the FIG. 3 image display apparatus.

5 In FIG. 4, reference numeral 201 designates a PC serving as an external signal source that supplies an image signal to the image display apparatus, and reference numeral 202 the image display apparatus having the whiteboard function. The image display
10 apparatus 202 includes the large-screen rear projection display. Further, reference numeral 203 designates a control signal input means that detects an image-plotting signal from the digitizer pen 105 and inputs a signal (control signal) according to the detected
15 image-plotting signal to the image display apparatus 202.

Reference numeral 204 collectively designates image output terminals of the PC, such as an analog VGA terminal, and digital terminals including a DVI
20 terminal, and an IEEE 1394 terminal, via which image signals are outputted. Reference numeral 205 collectively designates control signal input terminals of the PC 201, such as a USB terminal, an IEEE 1394 terminal, a serial terminal and a mouse terminal, via
25 which a coordinate signal obtained in the image display apparatus by conversion and use dependent-switching of a signal from the control signal input means 203 is

inputted to the PC 201 from the image display apparatus as the control signal.

Reference numeral 206 designates an operating system (OS)(1) of the PC 701, and reference numeral 207
5 an application program (1) which is one of application software programs executed on the PC 201. Actually, the OS(1) 206 and the application program(1) 207 are stored and exist as software programs in a storage medium for the PC 201. However, they are shown as
10 false images in FIG. 4 to represent their operations on the PC 201.

Reference numeral 208 collectively designates image signal input terminals of the image display apparatus, such as an analog VGA terminal, and digital
15 terminals including a DVI terminal, an IEEE 1394 terminal and a D terminal. Reference numeral 209 designates an input image signal processing section. When an input signal is an analog signal, the input image signal processing section 209 adjusts the input
20 image signal to a predetermined amplitude and to a predetermined DC level, and converts the same to a digital signal, while when an input signal is a digital signal, the section 209 performs conversion of the signal to a predetermined signal level and to a
25 predetermined color format, and other signal processing. Reference numeral 210 designates a resolution conversion section that performs conversion of the

resolution and frame rate of the image signal and like processing. The resolution conversion section 210 accommodates a variation in the input image due to a difference in the format of the image signal, and at
5 the same time performs suitable interpolating processing of the image signal adapted to the number of pixels on the display screen according to a display range set by the user, followed by delivering the resulting signal to an image synthesis section 211,
10 referred to hereinafter. The resolution conversion section 210 includes a memory device for storing image signals after conversion of the resolution and frame rate thereof.

Reference numeral 211 designates the image
15 synthesis section. The image synthesis section 211 switches between a whiteboard image-plotting signal from a whiteboard function plotting section 217 provided in the image display apparatus 202 and the image signal from the signal source inputted via the
20 terminal 208 and then subjected to the above-described signal processing, such as the resolution conversion, and carries out image synthesis based on the whiteboard image-plotting signal and the image signal when both signals are selected. The image synthesis section 211
25 includes a memory device for storing information of the synthesized image.

Reference numeral 212 designates an output image

processing section. The output image processing section 212 performs signal processing, such as gamma correction and division driving suitable for a device forming an image display section 213. Reference numeral 213 designates the image display section comprised of a reflective or transmission liquid crystal display, a direct-view type liquid crystal display, a self-emitting display including a cathode ray tube (CRT) and a laser display, a plasma display panel (PDP), an EL element, an LED, or a projection mirror device, and a drive circuit therefor.

Further, reference numeral 214 collectively designates control signal input terminals, such as a USB terminal, an IEEE 1394 terminal, a serial terminal and a mouse terminal. Each control signal input terminal 214 inputs a detection signal from the control signal input means 203 including the digitizer pen 105 to the image display apparatus 252. In the present embodiment, the following description will be given based on an illustrated example in which a control signal between the control signal input means 203 and the image display apparatus 202 and a control signal between the PC 201 and the image display apparatus 202 are signals conforming to the USB standard.

Reference numeral 215 designates a USB conversion section for decoding a USB signal into a coordinate signal. Reference numeral 216 designates a control

input coordinate conversion and control signal switching section (hereinafter simply referred to as "the control signal switching section 216"). The control signal switching section 216 selectively

5 determines whether the coordinate signal should be used as the whiteboard image-plotting signal, or as a signal for instructing a change in a boundary between a display area of the white board image-plotting signal and a display area of the image signal which are

10 displayed by the aforementioned synthesis, or as a control signal delivered to the PC 201, according to an instruction selected from a menu option displayed on the display screen, or an instruction inputted by using a button, not shown, provided on the image display

15 apparatus 202, or by using a button provided in the control signal input means 203, or according to coordinates of a position on the display screen designated by the control signal input means 203. The control signal switching section 216 also converts the

20 coordinates of the signal according to a use thereof. The above-mentioned selective determination according to the coordinates of a position on the display screen designated by the control signal input means 203 is carried out in the following manner: If a display area

25 of the white board image-plotting signal which is one of the two signals synthesized by the image synthesis section is indicated by the coordinates of the position,

the control signal from the control signal input means 203 is used for a signal for plotting an image by the whiteboard function (control signal; rewriting signal); if a display area of the image signal from the PC 201 inputted via the terminal 208 is indicated by the coordinates of the position, the same is used as the control signal (operation signal) delivered to the PC 201, and if a boundary between the two display areas is indicated by the coordinates of the position, the same is used for instructing a change in the display areas of the image displayed by the above-described synthesis.

Reference numeral 218 designates a memory section of the whiteboard function plotting section 217. The whiteboard function plotting section 217 specifies a memory address within the memory section 218 for data replacement, based on the coordinate signal delivered from the control signal input means 203 after having been selected as the whiteboard image-plotting signal and subjected to coordinate conversion by the control signal switching section 216. At this time, a method of arithmetic operation is selected in response to an instruction by a menu button, not shown, or an icon button, not shown, displayed on the display screen or by a button, not shown, provided in the body, not shown, of the image display apparatus 202 or attached to the control signal input means 203, and an arithmetic operation is performed on data after the data

replacement with reference to data before the data replacement. Now, a description will be given of an operation performed e.g. when a red pen icon and an eraser icon are displayed on a white display screen

5 within an image-plotting area realizing a color display using the three primary colors of red, blue and green, each with values of 0 to 255. With respect to coordinates of a signal delivered from the control signal input means 203 after the pen icon has been

10 selected, data at designated coordinates within a memory area storing red images has a value thereof replaced by the maximum value 255, regardless of the value of the data before the replacement. Further, when the values of respective red, blue and green data

15 are all 255 before data replacement, in memory areas storing blue images and green images, respectively, the blue data and the green data are each replaced by data having a value of 0, whereas in the other cases, blue data and green data remain displayed without

20 replacement. As a result, white portions of an image plotted by the pen are displayed in a manner written or painted in red, and the other color portions are displayed in colors obtained by mixing the red color and another color by the additive color process. For

25 instance, when a red line is plotted on a blue portion, red is mixed with blue, and the resulting color is magenta. If it is preferred that the white portions of

the image plotted by the pen are displayed in red, and the other color portions are displayed in mixed colors obtained by the subtractive color process, values of the respective colors calculated by using the data
5 before replacement are each stored in a corresponding one of the memory areas storing the respective red, blue and green images.

On the other hand, with respect to coordinates of a signal delivered from the control signal input means
10 203 after the eraser icon has been selected, data at designated coordinates within each of the memory areas storing the respective red, blue and green images has a value thereof replaced by the maximum value 255, regardless of the value of the data before the
15 replacement. As a result, portions plotted after selection of the eraser are displayed in white in a manner such that the plotted lines and the like are erased.

The above arithmetic operations may be performed
20 by hardware, i.e. by a logic circuit within a semiconductor device, or alternatively by software, i.e. by a program stored in a storage medium, not shown, which is executed by a microcomputer, not shown, within the image display apparatus 202.

25 A screen control section 219 controls an image display screen by using the coordinate signal selected and outputted by the control signal switching section

216 as the signal for controlling both a display area
for an image based on the image signal inputted via the
DVI terminal 208 and a display area for an image
plotted based on the whiteboard image-plotting signal
5 by the whiteboard function plotting section 217. The
screen control section 219 controls a resolution
conversion part of the resolution conversion section
210 based on the size, resolution and display position
of an image designated by the microcomputer, not shown,
10 and inputted via the DVI terminal 208, and reads out an
image with a size, a position and a resolution, which
are required for display, in proper timing with respect
to a synchronizing signal. Further, the screen control
section 219 controls the whiteboard function plotting
15 section 217 based on the size and display position of
the image designated by the microcomputer, not shown,
and plotted by the whiteboard function, and reads out
an image with a size and a position, which are required
for display, in proper timing with respect to the
20 synchronizing signal. Further, responsive to an
instruction from the microcomputer, not shown, the
screen control section 219 controls the image synthesis
section 211 to switch the mode of operation to a mode
for displaying only an image plotted by the whiteboard
25 function, a mode for displaying only an image inputted
via the DVI terminal 208, a mode for displaying a
synthesized image of the two images on a parent screen

and a child screen, or a mode for displaying a synthesized image of the two images on left and right screens.

Reference numeral 220 designates a filing section
5 for filing image data. The filing section 220 records
a desired image selected by the image synthesis section
211 onto a medium or transmits the image to an external
device. Reference numeral 221 designates a USB
conversion section for encoding image data transferred
10 from the filing section 220 and control data delivered
from the control signal input means 203 and selected as
the control signal for the PC 201 by the signal
switching section 216, into a signal conforming to the
USB standard. Further, reference numeral 222
15 designates a control signal output terminal, such as a
USB terminal, an IEEE 1394 terminal, a serial terminal
or a mouse terminal. In the present example, the USB
terminal is employed. From the control signal output
terminal 222, a coordinate signal obtained by
20 conversion and use dependent-switching of the signal
from the control signal input means 203 of the image
display apparatus 202 is outputted as the control
signal to the PC 201, and image data filed by the
filing section 220 is transmitted to the PC 201.

25 Although the USB conversion section 215 and the
USB conversion section 221 are shown as separate
sections in FIG. 4, actually in many cases, they are

provided as a one-piece USB semiconductor chip equipped with a HUB function. Therefore, in such a case, USB data can be directly transferred from the USB conversion section 215 to the USB conversion section 221 without being sent to the control signal switching section 216.

The overall operation of the image display apparatus 202 according to the present embodiment is controlled by the microcomputer, not shown, incorporated in the image display apparatus 202.

As described above, the image display apparatus 202 has an image processing section including the whiteboard function plotting section 217 for plotting an image based on the control signal from the control signal input means 203, and the memory section 218 as storage means used by the whiteboard function plotting section 217, which are separately provided in addition to the input image signal processing section 209 to which the image signal is inputted. The image processing section has the function of selectively displaying an image generated from the inputted image signal and an image plotted by the whiteboard function or synthesizing the two images and displaying the synthesized image. Further, the image display apparatus 202 is capable of causing the control signal switching section 216 to selectively determine whether the control signal from the control signal input means

203 should be used as a signal for image plotting by the whiteboard function, as a signal for changing a display area of the synthesized image, or as a control signal which is outputted to the PC 201 connected to the device 202, in response to an instruction selected from a menu option displayed on the display screen or a button in the body of the image display apparatus 202, or by a button attached to the control signal input means 203, or according to position information designated on the display screen by the control signal input means 203, thereby enabling the function of the PC 201 and the whiteboard function within the image display apparatus 202 to be operated on the same screen by the identical control signal input means 203.

Further, the image display apparatus 202 is capable of transmitting a whiteboard image or a whiteboard image synthesized with an input image signal to an external device or recording the same onto a recording medium. Therefore, an image plotted by the whiteboard function within the image display apparatus 202 can be outputted to the PC 201 and an external network connected to the PC 201. Consequently, even when no image signal is inputted, if the whiteboard function plotting section 217 alone is selected for use by the image synthesis section 211, it is possible to use the whiteboard function, so that a user who wants to use the whiteboard function alone does not have to

wait over a time period from the start of the PC 201 connected to the image display apparatus 202 and until a network to which the PC 201 belongs and the user are authenticated.

5 Further, the whiteboard function can be utilized without any knowledge of the PC 201 and the like, and hence the image display apparatus 202 realizes an apparatus which requires no complicated operation for such authentications and can be readily used even by a
10 child who is not able to operate a computer.

Moreover, the image display apparatus 202 is capable of displaying a screen of the PC 201 subjected to resolution conversion as a child screen within a whiteboard plotting screen, so that the whiteboard
15 function build into the image display apparatus 202 and the function of an image display apparatus for the PC 201 can be improved in a synergistic or cooperative manner.

Furthermore, since the whiteboard function is
20 separated from an application program on the PC 201 that requires authentication or the like, an environment demanding no security (e.g. the whiteboard function) and an environment ensuring security (e.g. the application program on the PC 201) can be separated
25 from each other, which makes it possible to use the image display apparatus 202 according to its use at a classroom or at a meeting. For example, at a classroom,

after children have discussed freely by using only the whiteboard function of the image display apparatus 202, a teacher logs on to the network through authentication of his PC 201 and sends a necessary file therefrom to
5 another PC 201 connected to the image display apparatus 202 to thereby allow a program to be started to read in the file. Then, the teacher carries out two-screen display of an image of the file on the PC 201 and images on the whiteboard screen plotted by the children,
10 and comments thereon. In this case, since the children do not need to operate the PC 201, there is no fear of an important file or data within the PC 201 being erroneously rewritten by the children.

Further, since an image inputted from the PC 201
15 and subjected to resolution conversion and an image plotted by the whiteboard function within the image display apparatus 202 can be synthesized with each other, it is not necessary to operate, on the PC 201, a special application program for synthesizing and
20 displaying the two images, and setting an environment for manipulating the two images on the same screen, which makes the image display apparatus 202 connectable to any PC 201. Even when an expositor uses a notebook PC of his/her own as the PC 201, it is not necessary to
25 install an application software program designed specially for the image display apparatus 202 on the notebook PC.

In addition, since an image plotted by the whiteboard function or an image synthesized from such a plotted image and an image from an input image signal can be transmitted to an external device or recorded onto a recording medium, and since operations in both an environment demanding no security (e.g. the whiteboard function) and an environment ensuring security (e.g. the application program on the PC 201) and control of display screen areas in the respective two environments can be performed in response to a signal from the control signal input means 203, it is possible to use the same image display apparatus and the same external input device to operate in a unified way the whiteboard function built into the body of the image display apparatus and the function of an application program executed by the PC which is on a different platform from the whiteboard function, thereby realizing a seamless environment.

For example, let it be assumed that workers of a company are discussing some matter in a casual atmosphere at their office while using the whiteboard function alone and that someone happens to come up with an interesting idea during the discussion. Then, if they want to keep the minutes and circulate the same, one of them starts a PC 201 to undergo authentication and switch the operation mode of the display device to the two-screen display mode for displaying both an

image by the whiteboard function and a screen of the PC 201. In this case, the switching of the screen mode, setting of the position and size of the screen area, and mouse control within the started PC 201 are all carried out by using a signal obtained by converting the control signal from the digitizer by the signal switching section 216. This allows all the operations to be performed on the same screen of the display apparatus by using the same digitizer pen 105. Further, since image data from the image synthesis section 211 is saved as it is in a file by the filing section 220 without being processed, and then transmitted as a packet via the same USB terminal via which the control signal is transferred, it is possible to have a discussion again with reference to the image by using a whiteboard facility realized by another application program or the like executed on the PC 201 or to distribute the file by attaching the same to an email as minutes by E-mail software.

In the present embodiment, an image inputted from the PC 201 via the image signal input terminal 208 can also be temporarily stored in a memory section other than the memory section 218 and then synthesized with an image from the memory section 218 by the image synthesis section 211.

Although in the present embodiment, the memory section 218 and the image signal processing section 209

are provided as two different processing sections separated in terms of hardware, the memory section 218 and the above other memory section may use different memory areas on the same recording medium. Further, 5 the function of the image-plotting part of the memory section 218 and that of the image signal processing section 209 can also be implemented by software on the same hardware, such as a CPU or a graphic IC. The present invention may be applied to such a case without 10 departing from the essential features of the present invention.

One of the objects of the present invention is to realize an image display apparatus which is capable of simultaneously displaying both a screen for performing 15 a function requiring authentication on a host PC and a screen for performing the whiteboard function requiring no authentication, thereby being flexibly adaptable to different uses of the apparatus e.g. between an expositor and auditors whose position is different from 20 that of the expositor in terms of security against unauthorized access. A further object of the present invention is to enable control of the PC and the image display apparatus and data exchange between the two by using common control means, such as a digitizer, for 25 the PC and the image display apparatus whose platform is different from that of the PC, thereby realizing a seamless presentation tool. These functions are

necessary not only to a large-screen display, but also to other types of image display apparatus in some cases.

In the following, a description will be given of an information processing apparatus using an image display apparatus according to a second embodiment of the present invention, with reference to drawings showing the same.

FIG. 5 is a view useful in explaining the whiteboard function of the information processing apparatus using the image display apparatus according to the second embodiment.

The image display apparatus of the second embodiment is applied to a portable information terminal having a whiteboard function implemented for personal use by circuitry allowing a software process to be executed by the same hardware such as a CPU or a graphic IC.

The portable information terminal shown in the figure functions as a single device having a normal whiteboard function when it is not connected to a PC, whereas when connected to the PC, it functions as a device which is capable of displaying a screen of the PC and makes it possible to control the PC by the same control means that controls the portable information terminal itself.

For example, a student who owns this portable information terminal usually utilizes the function of

the terminal as a single device, and when required, can use the function of the device as a terminal to refer to information on a PC screen transmitted from a teacher by comparing the same with information written
5 on a whiteboard of the device or to save the information from the teacher in the device.

In FIG. 5, reference numeral 301 designates the portable information terminal using the image display apparatus according to the second embodiment.

10 Reference numeral 302 designates a display screen of the portable information terminal 301, and reference numeral 303 a screen for realizing the whiteboard function built into the portable information terminal 301. Reference numeral 304 designates a digitizer pen
15 for use as an input device of this terminal, and reference numeral 305 a line plotted by the digitizer pen 304 by using the whiteboard function. Further, reference numeral 307 designates a PC, and reference numeral 306 designates an area on which a display
20 screen on the PC 307 connected to the portable information terminal 301 is displayed in a manner synthesized with the screen 303. Reference numeral 308 designates a display connected to the PC 307 via a cable. Images on the display 308 are also displayed on
25 the area 306. Reference numeral 309 designates a control cursor of the PC 307 displayed on the display 308, for controlling the PC 307.

Reference numeral 310 designates an image output terminal of the PC 307, while reference numeral 311 designates an image input terminal of the portable information terminal 301. Reference numeral 312
5 designates a cable for transmitting an image. The connection interface used here may be an analog VGA cable or a digital cable, such as a DVI cable, an IEEE 1394 cable or a USB cable, and not only a normal RGB serial signal and a TMDS signal but also a MPEG
10 compressed image signal and a packetized image signal are transmitted via the connection interface.

Reference numeral 313 designates an output terminal via which is outputted a control signal for transmitting an operation signal for operating the PC
15 307 or an image synthesized within the portable information terminal 301, as a file or packets, while reference numeral 314 designates an input terminal of the PC 307 via which the control signal is inputted into the PC 307. Further, reference numeral 315
20 designates a connection cable for use in transfer of the control signal. The interface for use in outputting the control signal may be a conventional serial communication interface, such as the RS232C interface, the IEEE 1394 interface or the USB interface.
25 Although in the illustrated example, the interface for image transmission and the interface for control signal output are provided by cables, it goes without saying

that radio transmission of the control signal may be employed without changing the essential features of the present invention.

In a first mode, the portable information terminal
5 301 functions alone as a personal information tool
having the whiteboard function as one of its functions.
The digitizer pen 304 and a control button arranged on
the body of the portable information terminal 301 are
used to select functions built into the portable
10 information terminal 301 or designate coordinates of a
plotted image for whiteboard plotting.

In a second mode, only the screen which is
displayed on the area 306 in FIG. 5 is displayed on the
whole display screen 302. In this case, the portable
15 information terminal 301 functions as a terminal of the
PC 307. More specifically, the digitizer pen 304 and
the control button on the body of the terminal 301 can
be operated similarly to an external mouse of the PC
307 to move a cursor which is displayed on the area 306
20 in a manner corresponding to the cursor 309 on the
display 308, in the same screen as the display 308. In
this mode, the platform of the portable information
terminal 301, such as an OS of the same, is hidden,
which makes the portable information terminal 301
25 appear as if it were operating on a software program
installed on the PC 307.

In a third mode, as shown in FIG. 5, the screen

for the whiteboard function and the display screen of the PC 307 are displayed in a synthesized manner. At this time, the screen of the PC 307 has been subjected to resolution conversion and a proper interpolating process according to the size of the area 306 on a child screen. In this mode, the digitizer pen 304 and the control button on the body of the terminal 301 are operated similarly to the external mouse of the PC 307 to move the cursor which is displayed on the area 306 in a manner corresponding to the cursor 309 on the display 308, on the area 306, and select functions built into the portable information terminal 301 or designate coordinates of a plotted image for whiteboard plotting, on the screen 303. Further, the digitizer pen 304 and the control button can be used to designate an area indicative of a boundary between the screen 303 and the area 306 to thereby change the size and position of the display area of each of the screen 303 and the area 306. In this mode, on the screen 303, the portable information terminal 301 operates on the platform, such as the OS within the terminal 301, whereas on the area 306, the terminal 301 operates as if operating on a software program executed by the PC 307, thereby making it possible to control the two apparatuses in different environments by the same or common control means. Further, the portable information terminal 301 can file a synthesized image

and store the file in the storage medium of the terminal 301 or can packetize the synthesized image and transmit the packet to the PC 307 via the connection cable 315 or the like, thereby sharing the synthesized
5 image with the PC 307.

FIG. 6 shows the construction of a control section of the FIG. 5 information processing apparatus.

In FIG. 6, reference numeral 401 designates a PC as an external signal source, while reference numeral
10 402 designates a portable information terminal using the image display apparatus according to the second embodiment. Reference numeral 403 designates control signal input means for detecting image-plotting signals from a digitizer pen 304 and buttons incorporated in
15 the portable information terminal 402 and inputting the detected signals.

In the PC 401, reference numeral 404 designates an image signal output terminal of the PC 401, and reference numeral 405 an input/output terminal for
20 control signals between the portable information terminal 402 and the PC 401. Reference numeral 406 designates an operating system (OS)(1) for controlling the PC 401, and reference numeral 407 an application (1) which is one of application software programs for
25 operation on the OS(1) 406.

In the portable information terminal 402, reference numeral 408 designates an input terminal for

image signals from the PC 401, and reference numeral 409 an input/output terminal for control signals between the portable information terminal 402 and the PC 401. Reference numeral 410 designates a CPU (central processing unit) of the portable information terminal 402, reference numeral 411 an operating system (OS) (2) for controlling the portable information terminal 402, and reference numeral 412 basic operation software operating on the OS(2) 411. The basic operation software 412 controls the internal operation of the portable information terminal 402. For example, an input image signal processing section, a memory control section, a decoder/encoder section, a control IF section, an output image processing section and a recording medium section, all described in detail hereinafter, have operations thereof controlled by the basic operation software 412. Reference numeral 413 designates an application program (2) which is one of application software programs operating on the OS(2) 411. Further, reference numeral 414 designates a whiteboard software program (2) which is one of application software programs operating on the OS(2) 411 to realize the whiteboard function. Reference numeral 415 designates a main memory section of the portable information terminal 402. Further, reference numeral 417 designates the input image signal processing section for decoding an image format of an

image inputted by the portable information terminal 402 via the image signal input terminal 408. This section also performs resolution conversion for converting the number of display pixels of the input image to the number of pixels in a display area on an image display section 424, referred to hereinafter, (resolution conversion device).

Reference numeral 419 designates a VRAM memory provided in addition to the main memory section 415 and used exclusively for image processing. The VRAM memory 419 is divided into three memory areas designated by respective reference numerals 420 to 422. Reference numeral 416 designates the memory control section (image synthesis device) for controlling a memory space within the portable information terminal 402. The memory control section 416 controls not only the main memory section 415 but also controls the operation of the VRAM memory 419 in response to an instruction by the CPU 410. Therefore, an image-plotting function of writing image-plotting information into the VRAM memory 419, which corresponds to the whiteboard function performed by the whiteboard software as described in detail hereinafter, and an image synthesis function of synthesizing an image plotted on whiteboard and stored in each VRAM area and an input image from the external PC with each other and storing the synthesized image in another memory area of the same VRAM are performed by

the memory control section 416.

Reference numeral 423 designates the output image processing section for converting an image signal transferred from the VRAM 419 to a format which can be displayed by the image display section 424. The image display section 424 is comprised of a reflective or transmission liquid crystal display, a direct-view type liquid crystal display, a self-emitting display (e.g. a CRT), a plasma display panel (PDP), an EL element, an LED, or the like. Reference numeral 425 designates the recording medium section for storing images synthesized by the VRAM 419, the application program (2), the basic operation software program, the whiteboard software program (2) and the like. Reference numeral 426 designates the control IF section (control signal input device) for inputting (coordinate) control signals (i.e. image-plotting signals) from the control signal input means 403. Further, reference numeral 427 designates a bus comprised of a control bus connecting the respective sections to each other and a data bus.

Reference numeral 418 designates the decoder/encoder for decoding or encoding signals, such as an IEEE 1394 signal and a USB signal, inputted or outputted via the control signal input/output terminal 409 between the portable information terminal 402 and the PC 401. The CPU 410 switches the use of a control signal from the control signal input means 403

according to an image display area and transmits the same to the PC 401 as a control signal via the decoder/encoder 418 (control signal switching device). Further, each image data synthesized by the VRAM 419 is
 5 also transmitted via the decoder/encoder 418 after having been filed.

FIGS. 7 to 9 shows a routine for an image display process which is executed by the portable information terminal.

10 In FIG. 7, when the portable information terminal 402 is turned on at a step S1, the OS(2) 411 and the basic operation software program 412 on the portable information terminal 402 are started at a step S2, whereby the portable information terminal 402 becomes
 15 usable. At this time, the CPU 410 cooperates with the memory control section 416 to read programs from the recording medium section 425 and executes the basic operation program by using the main memory 415. At the following step S3, it is determined whether or not an
 20 image input mode for inputting an image from the PC 401 has been selected.

If the image input mode has not been selected as a result of the determination at the step S3, i.e. if the first mode has been selected, the whiteboard software
 25 program(2) 414 is read from the recording medium section 425 and then executed on the CPU 410 at a step S4. As a result, coordinate control signals inputted

from the control signal input means 403 are read onto the CPU 410 via the control IF section 426, and at the same time, the memory control section 416 selects the area (2) 421 within the VRAM 419 to carry out

5 coordinate conversion and writing of data values at a step S5. Then, at a step S6, an image is transferred from the area (2) 421 within the VRAM 419 to the output image processing section 423, and subjected to image processing in a manner adapted to the output thereof,

10 followed by being displayed on the image display section 424. The image data in the area (2) 421 is saved in the recording medium section 425 as a file, or packetized on the CPU 410 and the main memory section 415 and encoded by the encoder/decoder 418 according to

15 the IEEE 1394 or USB standard, so as to be ready for transmission to the PC 401.

At the following step S7, it is determined whether or not mode switching has been performed. If mode switching has not been performed, the program returns

20 to the step S5, wherein image plotting by the whiteboard function is continuously carried out. If mode switching has been performed, the program proceeds to a step S8, wherein it is determined whether or not termination of the program has been selected. If the

25 termination has been not been selected at the step S8, the steps S3 et seq. are executed again, whereas if the termination has been selected, the program is

terminated.

If the image input mode for inputting an image from the PC 401 has been selected at the step S3, i.e. if the second mode has been selected, the external PC 401 is started in advance to effect setting of security and the like, followed by the program proceeding to a step S10.

At the step S10, it is determined whether or not the mode for synthesizing an image plotted by the whiteboard function and an image from the PC 401 with each other has been selected. If the synthesis mode has not been selected, the CPU 410 issues an instruction to display a display screen of the PC 401 based on the basic operation software program, whereby the display screen of the PC 401 inputted via the image signal input terminal 408 is subjected to a proper resolution conversion by the input image signal processing section 417, and then writing (3) of the resulting data into the area (1) 420 of the VRAM 419 is performed (step S11).

Then, at a step S12, signals read from the area (1) 420 of the VRAM 419 are transferred to the output image processing section 423 and subjected to image processing in a manner adapted to the output, followed by being displayed as a screen on the image display section 424. Further, at a step S13, the control signal from the control signal input means 403 is

subjected to coordinate conversion on the CPU 410 in a manner adapted to the display screen of the PC 401, and then encoded by the encoder/decoder 418 according to the IEEE 1394 or USB standard, followed by being
 5 transmitted to the PC 401 as the mouse control signal corresponding to the writing (3).

At the following step S14, it is determined whether or not mode switching has been performed. If mode switching has not been performed, the program
 10 returns to the step S11, wherein display of the operation screen of the PC 401 is continuously carried out. If mode switching has been performed, the program proceeds to a step S15, wherein it is determined whether or not termination of the program has been
 15 selected. If the termination has not been selected at the step S15, the steps S3 et seq. are executed again, whereas if the termination has been selected, the program is terminated.

If the image input mode has been selected at the
 20 step S3, and further the synthesis mode has been selected at the step S10, i.e. if the third mode has been selected, the external PC 401 is started, and setting of security and the like is performed, followed by the program proceeding to a step S16.

25 At the step S16, a whiteboard software program(2) 414 is read from the recording medium section 425 and operated on the CPU 410. Then, the CPU 410 issues an

instruction to capture the display screen of the PC 401.
As a result, at a step S17, the display screen of the
PC 401 inputted via the image signal input terminal 408
is subjected to a proper resolution conversion by the
5 input image signal processing section 417, and then
writing (1) of the resulting data into the area (1) 420
(another memory device) of the VRAM 419 is performed.
Further, the plotting control signal from the control
signal input means 403 is read onto the CPU 410 via the
10 control IF section 426, and at a step S18, the memory
control section 416 selects the area (2) 421 (memory
device) within the VRAM 419 and performs coordinate
conversion and writing (2) of the data values.

At the following step S19, image information
15 written in the area (1) 420 and area (2) 421 of the
VRAM 419, respectively, are subjected to an arithmetic
operation for image synthesis on the memory control
section 416 according to an instruction from the CPU
410, and then the result of the image synthesis is
20 written onto the area (3) 422 (still another memory
device) of the VRAM 419. Then, the area (3) 422 is
selected, and the synthesized image is transferred from
the area (3) 422 to the output image processing section
423, wherein the image is subjected to image processing
25 in a manner adapted to the output, followed by being
displayed on the image display section 424. The image
data in the area (3) 422 is saved in the recording

medium section 425 as a file, or packetized on the CPU 410 and the main memory section 415 and then encoded by the encoder/decoder 418 according to the IEEE 1394 or USB standard, so as to be ready for transmission to the PC 401.

Further, at a step S20, the use of the signal from the control signal input means 403 is switched according to an image area corresponding to the signal, and a signal that forms part of the synthesized image from the control signal input means 403 and designates a display area for the image from the PC 401 is subjected to coordinate conversion in a manner corresponding to the position of the display screen. Then, the signal subjected to the conversion is encoded by the encoder/decoder 418 according to the IEEE 1394 or USB standard, followed by being transmitted to the PC 401 as the mouse control signal corresponding to the writing (1).

At the following step S21, it is determined whether or not mode switching has been performed. If mode switching has not been performed, the program returns to the step S17, wherein the operation of the PC 401 and plotting on the whiteboard are continuously carried out in a manner adapted to the coordinates of the display area. If mode switching has been performed, the program proceeds to a step S22, wherein it is determined whether or not the termination of the

program has been selected. If the termination has not been selected at the step S22, the steps S3 et seq. are executed again, whereas if the termination has been selected, the program is terminated.

5 According to the process shown in FIGS. 7 to 9, the portable information terminal 402 is capable of operating as a single device having the whiteboard function, and when a network to which the PC belongs and the user of the PC are authenticated, the portable
10 information terminal 402 can also be utilized as a terminal for the PC 401. That is, the portable information terminal 402 can be used both in an environment demanding no security (e.g. the whiteboard function) and in an environment ensuring security (e.g.
15 the application program on the PC 201), so that it can be used in a manner adapted to a selected one of the two kinds of environments. This increases the range of the use of the portable information terminal 402 in places, such as educational institutions and meetings
20 or conferences.

 In particular, since an image inputted from the PC 401 and subjected to resolution conversion is synthesized with an image plotted by the whiteboard function built into the portable information terminal
25 402, it is not necessary to operate any special application software program on the PC 401, which makes it possible to connect the portable information

terminal 402 to any PC without any need to select a host PC for connection with the portable information terminal 402. Thus, the portable information terminal 402 can be connected to various types of devices

5 anywhere, and hence the range of its use is increased. Further, the portable information terminal 402 can be connected to such devices irrespective of a difference between platforms, such as OS's.

Moreover, since an image plotted by the whiteboard
10 function or an image synthesized from the plotted image and an input image can be transmitted to an external device or recorded onto a recording medium, and since operations in both an environment demanding no security (e.g. the whiteboard function) and an environment
15 ensuring security (e.g. the application program on the PC 201) and control of display screen areas in the respective two environments can be performed, it is possible to use the same image display section and the same control signal input means 403 to carry out in a
20 unified manner operations of the function built into the body of the image display apparatus and the function of an application program executed on the PC which are on different platforms, thereby realizing a seamless environment.

25 In the above described embodiments, the image signal input terminal, such as an analog VGA terminal or a DVI terminal, via which a signal is inputted from

an external signal source, such as a PC, and the control terminal of the external signal source, such as a USB terminal or an IEEE 1394 terminal, are shown separately from each other. Since image signals, however, are more likely to be transmitted in packets after being compressed e.g. in accordance with the MPEG standard or partially rewritten, it is expected that transmission of image signals will be performed via a USB terminal or an IEEE 1394 terminal as well in the near future. Needless to say, the present invention can be applied to such a case.

For example, when an external signal source, such as a PC, and an image display apparatus or an information processing apparatus using the image display apparatus are connected to each other by a single IEEE 1394 cable, an image signal from the external signal source and a control signal to the external signal source are sent and received by using the same IEEE 1394 decoder and encoder. In this case, the image signal outputted from the IEEE 1394 decoder is decompressed e.g. from its MPEG compressed state and subjected to the aforementioned resolution conversion, and then synthesized with a screen for the whiteboard plotting function. On the other hand, the control signal from the digitizer pen or the like is switched by the CPU and an internal software program to a signal for rewriting by the whiteboard plotting section or to

operation information to be sent to the external signal source. Further, the control signal is also used to convert by the CPU and the internal software program from coordinates in a display area on the display
5 screen after the resolution conversion to coordinates corresponding to the image before the resolution conversion, and the results of the conversion are then converted to a transmission signal by the IEEE 1394 encoder, and the transmission signal is transmitted to
10 the external signal source.

Although in the above described embodiments, the external signal source and the image display apparatus or the information processing apparatus are connected to each other by a cable, it goes without saying that
15 radio transmission may be employed without changing the essential features of the present invention.

Further, the objects of the present invention can also be achieved by supplying a system or an apparatus with a storage medium storing software program modules
20 for realizing the above embodiments. In this case, the program modules read from the storage medium achieve the novel functions of the present invention, and the storage medium storing the program modules constitutes the present invention.

25 In the above embodiments, the program modules are stored in a recording medium section, not shown, of the image display apparatus 202 or in the recording medium

section 425 of the portable information terminal 402. The storage medium for supplying the program modules may be a floppy disk, a hard disk, an optical memory disk, a magneto-optical disk, a CD-ROM, an MO, a CD-R, 5 a DVD, a magnetic tape, a nonvolatile memory card, or the like. However, the storage medium is not limited to a specific one, and any medium which is capable of storing the above program modules can be employed.

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218